ZITHA TECH SPECIALTY CABLES (Pty) Ltd

Pigtail winding reel size



Overview

The reels have a standard central bore of 127 mm (5 inch) in diameter. Other diameters can also be supplied by means of additional inserts. Reel designations consist of the series description (LM or EM), the flange diameter, and the total outer width of the reels. OUTER WIDTH The outer width of the reels is normally the winding width (L2) plus 2x. For a good estimate, you need to have four numbers: the diameter of the core of the reel (the hub), the outer diameter of the rolled-up tape, the thickness of the carrier tape and the distance that the components are spaced from each other on the tape. For ease of measurement, what we measure. ** Fill diameter is the Flange diameter less 2″ (which allows for an inch of clearance between flange edge and wire).

Article Content

MOTOR POWERED CABLE REELS

ASSEMBLY When attaching the motor-powered cable reel to the consumer, make sure that the assembly frames or the foot-mounted gears have a level surface. In order to guarantee the smooth

Reel Capacity Calculator v1

Reels has two calculation options Capacity and Size; Capacity calculates the length of pipe or cable that can be accommodated within the outside diameter of the

A Method to Calculate the Capacity of a Reel or

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

It is often necessary to determine how much of a given cable or wire will fit onto a spool or reel. This article provides a relatively simple method to calculate the

Contact Us

Continue your research online:

Website: https://zithatech.co.za
Technical inquiry: https://zithatech.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved