
Slovenia E2000 connectors low-temperature resistant directly supplied by manufacturer




Overview

For harsh environmental conditions, Diamond partnership offers specialised E2000 connectors with extended temperature range from −40°C to +85°C, ideal for outdoor and industrial installations.

Key Takeaways

The E2000 fiber optic connector meets the working environment of -40-85 °C, with an average of more than 500-1000 insertion and removal tests, with stable performance and reliable quality. Operating temperature□-40-85℃ Insert-pull test□500-1000 times Multiple styles available. The E-2000® connector, invented by DIAMOND, delivers unmatched reliability and precision in fiber-optic interconnects - making it the ideal choice for critical transmission points across telecom, industrial, medical, and more applications. By checking this box I confirm that I have read the Privacy. to the increasingly customer demands. Diamond's two-component ferrule includes, a zirconium-ceramic sleeve and a titanium insert, that allows for the centering of the fiber core with the mechanical axis of. In addition to high perform-ance, the E-2000TM offers safety and time-savings. E2000 products include simplex and duplex versions. The E-2000 Connector Series is one of the few fiber optic connectors featuring a.



© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

Article Content

E-2000® Connector | High-Performance Fiber Optics

The E-2000® connector, invented by DIAMOND, delivers unmatched reliability and precision in fiber-optic interconnects - making it the ideal choice for critical

DIAMOND E-2000 Fiber Optic Components

This system is composed of a flange which provides an internal connection via a FC or Mini-AVIM style connector and a wide range of interchangeable adapters including the E-2000TM, FC, SC, ST and

Diamond E2000 Connectors | Professional Fibre Standards

For harsh environmental conditions, Diamond partnership offers specialised E2000 connectors with extended temperature range from −40°C to +85°C, ideal for outdoor and industrial installations.

Optical connector

Find out all of the information about the DIAMOND SA product: optical connector E-2000® series. Contact a supplier or the parent company directly to get a quote or

Connector Family E-2000TM

E-2000TM Hybrid Adapters allow connections between the E-2000TM connector and FCPC, FLSA or FSC connectors. All Hybrid Adapters are equipped with a slotted zirconia ceramic sleeve. The

E2000 Fiber Optic Connector : sFiberOptic

The E2000 fiber optic connector meets the working environment of -40-85 °C, with an average of more than 500-1000 insertion and removal tests, with stable

LSH (E-2000) Connector

The mechanical and colour coding system allows fast and secure installation of connectors and adapters, ensuring mating without risk of confusion. Connectors and adapters without coding are still

E-2000 Connector

The E-2000™ Connector offers a spring-loaded shutter mechanism that protects the ferrule end-face from scratches and dust while locking out potentially eye

E2000 Optical Fiber Connectors | HYC Co., Ltd

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

The E2000 connector provided by HYC has the advantages of more convenient insertion and removal, low insertion loss and high compressive strength. It is widely used in telecom networks,

DIAMOND E-2000 Fiber Optic Components

Diamond PS connectors are based on contacted expanded beam technology; where a section of graded index fiber is spliced as a collimating lens, which enlarges the beam diameter and reduces power

E2000 Connectors: Premium Fibre Standards | Fiber Products

Diamond E2000 connectors set new standards in fibre optic installation. Swiss precision, integrated safety, superior optical performance for FTTH and PON networks.

E2000 Multimode Fiber Optic Connectors

E2000 fiber optic connectors and related products include both single mode and multimode types. There are single mode E2000/UPC connector, single mode

E-2000® Connector | High-Performance Fiber Optics

The E-2000® connector by DIAMOND - inventor of this reliable, high-performance fiber optic solution - offers low insertion loss and multiple interface options for

E2000 Connectors for Government & Military Networks

E2000 connectors deliver proven security and reliability for government and military fibre optic infrastructure. Swiss precision, 5-year warranty, European manufacture.

Diamond E2000 Connectors | Professional Fibre Standards

Diamond E2000 premium connectors deliver 75dB return loss, automatic protective caps, and 5-year warranty for FTTH deployment. Swiss precision quality, German manufacturing.

E-2000 PS Diamond connectors and adapters

a section of graded index fibre is introduced as a collimating lens, which enlarges the beam diameter and reduces power density at the connector interface all of

E2000 Fiber Optic Connectors

E2000 fiber optic connector features Secure transmission of high bit-rate protocols Zirconia ceramic ferrule fully protected by spring loaded shutter Push-pull locking mechanism for easy installation

Fiber Optic Connector | Fiber Connector | E2000

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

Fiber optic connector is an important components used in the fiber optic network. It is also the key part used in fiber optic patch cords and fiber optic pigtails. E2000

Contact Us

Continue your research online:

Website: https://zithatech.co.za
Technical inquiry: https://zithatech.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved