The output of the Huijue switch s optical port is 0



Overview

The switch port may be faulty, or the optical transceiver may be overheated. If the optical module is installed on a GE port, run the display interface GigabitEthernet x/x/x command to check information about the port, including the rate and wavelength. Note: indicates the type and number of the interface where the module is. Problem: All optical ports cannot be connected, and the indicator lights are not on. Solution: To solve this problem, you can follow these steps: Check if the fiber and optical modules are compatible. This is tested using NetEngine40E Universal Service Router or NE40E running version 8. traffic was very slow or there was no data transmission at all?

Did you manage to diagnose the problem and find a. Check “Alarm information” section for warnings, LOS Alarm means no inbound signal, execute display this to check shutdown mode, execute undo shutdown if necessary. 2 Show transceiver power Receiving power too low (If Current RX Power < Default RX Power Low Threshold): May cause port down or packet.



© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

Article Content

Typical Troubleshooting Cases of Optical Module

Check whether the optical module is a Huawei-certified one. If not, replace it with a Huawei-certified optical module. If the optical module is installed on a GE port, run the display interface

Troubleshooting for Optical Modules on Huawei Switch

Check whether the optical module is Huawei-certified. If it is not certified by Huawei, replace it with a Huawei certified one. Remove and reinstall the optical module. If

How To Read Optical Module Information On Huawei Switches

The output includes interface rate, module type, link status (the state being UP is a prerequisite for normal operation) and traffic statistics, which can be used for troubleshooting.

Optical Module Solutions for Huawei S5700/S5720 Series Switches

Problem: All optical ports cannot be connected, and the indicator lights are not on. Solution: To solve this problem, you can follow these steps: Check if the fiber and optical modules

Checking TX / RX optical power for Huawei Switches and Routers

Here is an example on how to query or display optical power of an interface in a Huawei Router. This is tested using NetEngine40E Universal Service Router or NE40E running version 8.x OS. display

5 troubleshooting tips for connecting the SFP''s

Have you ever tried to plug an optic SFP+ transceiver into an SFP+ port to discover that the connection didn''t work, i.e. traffic was very slow or there was no data

How to Troubleshoot transceiver issue in Huawei switch/router/devices

Receiving power too high (Current RX Power > Default RX Power High Threshold): May caused by using long distance module in short distance, add Optical attenuators/Fiber optic

Optical Module Solutions for Huawei S5700/S5720 Series Switches

When using switches, we may encounter many confusions, such as what types of optical modules are needed for different models of Huawei switches, and how to resolve issues encountered

Optical Interface Interconnection Is Abnormal on CE Switches ...

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

After an SFP-GE copper or optical module is installed on a GE or 10GE optical interface, or a high-speed cable is installed on a 40GE optical interface, the interface works in auto-negotiation

Troubleshooting Optical Module Issues

Troubleshooting Optical Module Issues Symptom An optical port cannot go Up. The optical module cannot be properly identified and optical module information cannot be obtained. After

100G port interface between CE6870-24S6CQ-EI and USG6716E

By default, the FEC mode of a 100GE interface is enabled or disabled based on the optical module adaptation mode. When the optical module is QSFP28-100G-SR4, the FEC mode of

Troubleshooting for Optical Modules on Huawei Switch

When this optical module uses OM3 multimode optical fibers, its transmission distance is 0.3 km. The optical modules used on both ends must have the same

how to display power of optical module

fiber – uses the optical interface. As you can see in the above output, port mode is COMBO AUTO, SFP module has been inserted and current work mode is automatically chosen as

Checking 100GE Transmit (TX) and Receive (RX) Optical Power on

For checking transmission links on Huawei Routers, it is good to know how to find out the optical power of 100GE modules or interfaces for troubleshooting and making sure the desired or

What Can I Do If a Message Is Displayed Indicating that an Optical ...

Run the display transceiver command to check the value of the Transceiver Type field in the command output. This field indicates whether the rate of the optical module installed on the port matches the

port is disconnected due to optical module faulty

As per checked the log, it was found that the host port was disconnected, This alarm indicates the port and switch has been disconnected. Hence, we would advise you to perform cross

Setting Optical Power Alarm Thresholds

Setting Optical Power Alarm Thresholds Context You can set optical power alarm so that the device generates alarms if the transmit or receive power of an optical module exceeds a threshold. An alarm

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved

How To Read Optical Module Information On H3C Switches

The following uses the Moduletek QSFP-40G-LR4 module connected to an H3C S6820 switch as an example to introduce how to read information of the connected optical module on an H3C switch.

Contact Us

Continue your research online:

Website: https://zithatech.co.za
Technical inquiry: https://zithatech.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ZITHA TECH SPECIALTY CABLES (Pty) Ltd - All rights reserved